

HIGEN		INDUCTION MOTOR DATA SHEET		2.2 kW - 8 P	
MODEL: KMI-03HK9		CUSTOMER :		REV. NO :	
APPLICATION:		PROJECT NAME:		QUANTITY :	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		132S		OUTPUT 2.2 kW	
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES 8 POLES		
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE		
	<input type="checkbox"/> Increased Safety Exp.-proof		<input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y- <input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F <input type="checkbox"/> SOFT-STARTER		
PROTECTION IP 44		STARTING METHOD			
METHODS OF COOLING <input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/> AO					
FREQUENCY 60 Hz		RATED VOLTAGE 220 V 380 V V			
PHASE 3 PHASE		CURRENT			
SERVICE FACTOR 1.15		NO LOAD		A A A	
INSULATION CLASS B CLASS		FULL LOAD		12.2 A 7.1 A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)		STARTING		79.2 A 45.8 A A	
RES. METHOD 85		EFFICIENCY			
THERMO. METHOD		AT 1/2 LOAD		% %	
LOCATION <input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD		% %	
ALTITUDE 1000 m		AT FULL LOAD		79.0 %	
HUMIDITY 80 %		POWER FACTOR			
AMBIENT TEMPERATURE -10-40		AT 1/2 LOAD		% %	
RATING <input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD		% %	
NEMA DESIGN B		AT FULL LOAD		60.0 %	
MOUNTING <input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD)		850 rpm	
BEARING	TYPE BALL		TORQUE		
	DEW-DE 6208ZZ/6206ZZ		FULL LOAD 2.52 kg-m 100%		
	LUBRICANT GREASE		LOCKED ROTOR 3.53 kg-m 140%		
COUPLING METHOD <input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		BREAKDOWN		4.54 kg-m 180%	
SHAFT		NOISE LEVEL		62.0 dB(A)	
EXTENSION SINGLE		VIBRATION		15.0 μm	
EXTERNAL THRUST		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
TERMINAL BOX		(AT DIRECT ON-LINE)		48.8 kg-m ²	
MAIN <input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> NO		Motor GD ²		0.1530 kg-m ²	
AUX. <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT		62.0 kg	
BOX LOCATION LEFT		PAINTING		MUNSELL NO. 7.1B4.0/0.9(GRAY)	
APPLICATION STANDARDS IEC, KS		THICKNESS		<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
NOTE		REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.		1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
FC : FAN COOLED SC : SELF COOLED		DATE	PREPARED	CHECKED	APPROVED
		2008.04.02	S.M.KIM	J.H.JO	H.J.KIM