

HIGEN		INDUCTION MOTOR DATA SHEET		1.5 kW 4 P FF165	
MODEL: KMH-02HK1F		CUSTOMER :		COIL SPEC NO.:	
APPLICATION:		PROJECT NAME:		REV. NO : 0	
				QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		FF165		OUTPUT 1.5 kW	
ENCLOSURE		☐ DRIP PROOF		POLES 4 POLES	
		☒ TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		☐ Increased Safety Exp.-proof		☒ D.O.L ☐ Y-Δ	
PROTECTION		IP 55		STARTING METHOD	
METHODS OF COOLING		☐ SC ☒ FC ☐ NV		☐ REACTOR (%TAP) ☐ V.V.V.F	
				☐ VECTOR-DRIVE	
PHASE		3 PHASE		RATED VOLTAGE 220 V 380 V	
SERVICE FACTOR		1.15		FREQUENCY 60 Hz	
INSULATION CLASS		F CLASS		CURRENT	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD A A	
RES. METHOD		105 deg		FULL LOAD 5.9 A 3.4 A	
THERMO. METHOD		deg		STARTING 44.5 A 25.8 A	
LOCATION		☒ INDOOR ☐ OUTDOOR		EFFICIENCY	
ALTITUDE		1000 m		AT 1/2 LOAD %	
HUMIDITY		80 %		AT 3/4 LOAD %	
AMBIENT TEMPERATURE		-10~40 °C		AT FULL LOAD 84.0 %	
RATING		☒ CONT. ☐ %ED		POWER FACTOR	
NEMA DESIGN		B		AT 1/2 LOAD %	
MOUNTING		☐ B3 ☒ B5 ☒ V1 ☐ B3B5		AT 3/4 LOAD %	
BEARING		TYPE BALL / BALL		AT FULL LOAD 79.0 %	
		DEIN-DE 6205ZZ / 6204ZZ		SPEED (AT FULL LOAD) 1730 rpm	
		LUBRICANT GREASE		TORQUE	
COUPLING METHOD		☒ DIRECT ☐ V-BELT		FULL LOAD 0.84 kg-m 100%	
ROTATION(Facing Drive End)		☐ CW ☒ CCW		LOCKED ROTOR 1.60 kg-m 190%	
SHAFT				BREAKDOWN 1.69 kg-m 200%	
EXTENSION		SINGLE		NOISE LEVEL 67.0 dB(A)	
EXTERNAL THRUST		-		VIBRATION 30.0 μm	
TERMINAL BOX				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
MAIN		☒ STEEL ☐ AL ☐ CAST		(AT DIRECT ON-LINE) 6.0 kg-m ²	
AUX.		☐ YES ☒ NO		Motor GD ² 0.0174 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT 28 kg	
APPLICATION STANDARDS		KS.IEC		PAINTING	
				MUNSELL NO. 5PB 2.5/8	
				THICKNESS ☒ STANDARD ☐ μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-KMH-02HK1F		
WINDING			SPEED-TORQUE CURVE ST-KMH-02HK1F		
TYPE			TERMINAL BOX DIMENSION TB-KMH-02HK1F		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			2. HIGH EFFICIENCY MOTOR.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE					
IN ACCORDANCE WITH HIGEN MOTOR STANDARD.					
TE : TOTALLY ENCLOSED		DP : DRIP PROOF	DATE	PREPARED	CHECKED
FC : FAN COOLED		SC : SELF COOLED	2015-07-13	S.D.YUN	S.D.YUN
					APPROVED
					K.I.HA