



INDUCTION MOTOR DATA SHEET

7.5 kW 4 P 132M

MODEL:		CUSTOMER :		COIL SPEC NO.:		REV. NO : 0	
APPLICATION:		PROJECT NAME:				QUANTITY : SETS	
GENERAL DATA				PERFORMANCE DATA			
FRAME NO.		132M		OUTPUT		7.5 kW	
ENCLOSURE		☐ DRIP PROOF		POLES		4 POLES	
		☒ TOTALLY ENCLOSED		ROTOR TYPE		SQUIRREL CAGE	
		☐ Increased Safety Exp.-proof		STARTING METHOD		☒ D.O.L ☐ Y-△	
PROTECTION		IP 55				☐ REACTOR (%TAP) ☐ V.V.V.F	
METHODS OF COOLING		☐ SC ☒ FC ☐ NV				☐ VECTOR-DRIVE	
PHASE		3 PHASE		RATED VOLTAGE		220 V 380 V	
SERVICE FACTOR		1.15		FREQUENCY		60 Hz	
INSULATION CLASS		F CLASS		CURRENT			
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD		A A	
				FULL LOAD		27.5 A 15.9 A	
				STARTING		178.9 A 103.6 A	
LOCATION		☒ INDOOR ☐ OUTDOOR		EFFICIENCY			
ALTITUDE		1000 m		AT 1/2 LOAD		% %	
HUMIDITY		80 %		AT 3/4 LOAD		% %	
AMBIENT TEMPERATURE		-10~40 °C		AT FULL LOAD		91.7 %	
RATING		☒ CONT. ☐ %ED		POWER FACTOR			
NEMA DESIGN		B		AT 1/2 LOAD		% %	
MOUNTING		☒ B3 ☐ B5 ☐ V1 ☐ B3B5		AT 3/4 LOAD		% %	
BEARING		TYPE BALL / BALL		AT FULL LOAD		78.0 %	
		DEIN-DE 6208ZZC3 / 6206ZZC3		SPEED (AT FULL LOAD) 1750 rpm			
		LUBRICANT GREASE		TORQUE			
COUPLING METHOD		☒ DIRECT ☐ V-BELT		FULL LOAD		4.17 kg-m 100%	
ROTATION(Facing Drive End)		☐ CW ☒ CCW		LOCKED ROTOR		6.68 kg-m 160%	
SHAFT				BREAKDOWN		8.35 kg-m 200%	
EXTENSION		SINGLE		NOISE LEVEL 77.0 dB(A)			
		EXTERNAL THRUST -		VIBRATION 30.0 μm			
TERMINAL BOX				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
MAIN		☒ STEEL ☐ AL ☐ CAST		(AT DIRECT ON-LINE)		29.3 kg-m ²	
AUX.		☐ YES ☒ NO		Motor GD ²		0.1434 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT		82 kg	
APPLICATION STANDARDS		KS.IEC		PAINTING		MUNSELL NO. 5PB 2.5/8	
				THICKNESS		☒ STANDARD ☐ μm	
ACCESSORIES (OPTIONAL)				SUBMITTAL DRAWINGS			
TEMPERATURE DETECTOR				OUTLINE DIMENSION		DW-132MTFCHLS-2	
WINDING		NO		SPEED-TORQUE CURVE		ST-P7.5KK1T132M-2	
		TYPE -		TERMINAL BOX DIMENSION		TB-MS132NZ-1	
BEARING		NO					
		TYPE -					
SPACE HEATER		NO					
RATING		-					
NOTE				REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.				1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN MOTOR STANDARD.				2. PREMIUM EFFICIENCY MOTOR. (IE3)			
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE		PREPARED	
FC : FAN COOLED		SC : SELF COOLED		2016-04-07		O.S.KANG	
				CHECKED		APPROVED	
				K.I.HA		K.I.HA	