

HIGEN		INDUCTION MOTOR DATA SHEET		18.5 kW 6 P 180L	
MODEL: KMH-25HU8		CUSTOMER :		COIL SPEC NO.:	
APPLICATION:		PROJECT NAME:		REV. NO : 0	
				QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		180L		OUTPUT 18.5 kW	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 6 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-	
PROTECTION		IP 55		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> REACTOR ( %TAP) <input type="checkbox"/> V.V.V.F	
PHASE		3 PHASE		<input type="checkbox"/> VECTOR DRIVE	
SERVICE FACTOR		1.15		RATED VOLTAGE 380 V V	
INSULATION CLASS		F CLASS		FREQUENCY 60 Hz	
TEMP.RISE AT FULL LOAD (at S.F 1.0)		CURRENT			
RES. METHOD		105 deg		NO LOAD A A	
THERMO. METHOD		deg		FULL LOAD 39.0 A A	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		STARTING 292.9 A A	
ALTITUDE		1000 m		EFFICIENCY	
HUMIDITY		80 %		AT 1/2 LOAD %	
AMBIENT TEMPERATURE		-10~40		AT 3/4 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT FULL LOAD 91.7 %	
NEMA DESIGN		B		POWER FACTOR	
MOUNTING		<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 1/2 LOAD %	
BEARING		TYPE BALL / BALL		AT 3/4 LOAD %	
		DEW-DE 6312ZZ / 6309ZZ		AT FULL LOAD 78.5 %	
		LUBRICANT GREASE		SPEED (AT FULL LOAD) 1170 rpm	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		TORQUE	
ROTATION(Facing Drive End)		<input type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		FULL LOAD 15.4 kg-m 100%	
SHAFT		LOCKED ROTOR 21.6 kg-m 140%			
EXTENSION		SINGLE		BREAKDOWN 27.7 kg-m 180%	
EXTERNAL THRUST		-		NOISE LEVEL 77.0 dB(A)	
TERMINAL BOX		VIBRATION 30.0 $\mu$ m			
MAIN		<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST		ALLOWABLE LOAD GD <sup>2</sup> REFERRED TO MOTOR SHAFT	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		(AT DIRECT ON-LINE) 227.0 kg-m <sup>2</sup>	
BOX LOCATION		LEFT (Viewed from Drive end)		Motor GD <sup>2</sup> 1.0786 kg-m <sup>2</sup>	
APPLICATION STANDARDS		KS.IEC		MOTOR APPROX. WEIGHT 195 kg	
				PAINTING	
				MUNSELL NO. 5PB 2.5/8.0	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> $\mu$ m	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION ST-KMH-25HU8		
WINDING			SPEED-TORQUE CURVE DW-KMH-25HU8		
TYPE			TERMINAL BOX DIMENSION TB-180FR STEEL		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN MOTOR STANDARD.			2. HIGH EFFICIENCY MOTOR.		
TE : TOTALLY ENCLOSED DP : DRIP PROOF			DATE		
FC : FAN COOLED SC : SELF COOLED			PREPARED		
			CHECKED		
			APPROVED		
			2015-07-16		
			H.S.LEE		
			K.I.HA		
			K.I.HA		